



TILE ADHESIVE POWDER

Technical Datasheet

TA 200 Tile Adhesive Powder

Factory:



+985832933436



+989029355917

Office:



+985832933253



+989368376747



www.maxilrad.com



info@maxilrad.com



INTRODUCTION

This product is a type of inorganic portland cement that is modified with polymers and contains polypropylene fibers. This powder with higher adhesion force is also used for anti-moisture, anti-leakage.

CHARACTERS

- Short time to be solid, easy to construct. No need for tools.
- Anti-damp, anti-leaking, higher adhesive force.
- Non-toxic, friendly to the environment. Can be used in the domestic water projects.
- Anti-aging, high tensile strength, good ability to stop water pressure.

Uses

- Bathroom, kitchen floor, moisture-proof, leak-proof and waterproof walls.
- Gluing pool ceramic tiles.
- Gluing building stone.

Factory:



+985832933436



+989029355917

Office:



+985832933253



+989368376747



www.maxilrad.com



info@maxilrad.com

MAXILRAD

USE AMOUNT

-Mixed with water to use.

PACKAGE

10kg Bag/1000kg JumboBag



TEMPERATURE CONTROL

- Not suggested to apply under 5°C.
- Surface dry time is 8h at 23°C.
- Storage temp 5°C to 50°C.
- Far away from objects whose temp is higher than 80°C.

APPLICATION

After mix with water uniformly with ration 10:3-4,the Kingkong could be scraped on the concrete cracks and joints immediately.The mixture will release much heat during this period and becomes hard to stop the leakages.

CLEANING

Clean the application tools with water once work finished.

Factory:

 +985832933436

 +989029355917

Office:

 +985832933253

 +989368376747



www.maxilrad.com



info@maxilrad.com

MAXILRAD



Factory:



+985832933436



+989029355917

Office:



+985832933253



+989368376747



www.maxilrad.com



info@maxilrad.com